

FREE



Gas or wood-burning fireplace with handmade majolica surround.

SURROUND WEIGHT: 76 kg

GAS BURNING (NATURAL GAS OR LPG) IG 90

FIREBOX: in Aluker®

INLET: in grey enamelled steel

GLASS: ceramic heat resistant up to 750°C

FUNCTION CONTROL: remote control

CERAMIC LOGS: standard supply

HEATING: convection and radiation

FLUE GAS OUTLET: concentric pipe Ø 10/15 cm

FIREBOX HEAT OUTPUT: 9.5 kW (Natural gas)

9.5 kW (LPG)

THERMAL EFFICIENCY: 80% (Natural gas)

75% (LPG)

CONSUMPTION AT RATED HEAT OUTPUT:

 $0.90 \text{ m}^{3}/\text{h}$ (Natural aas)

720 g/h (LPG)

WEIGHT: 90 ka

RATED HEAT OUTPUT: 6.8 kW (Natural gas)

6.4 kW (LPG)

TYPE-EXAMINATION: EC certification E0780

OPTIONAL ACCESSORIES:

- river pebles
- height regulation kit

WOOD BURNING ME 90/44 INLET: in enamelled steel

FIREBOX: in Aluker ®

GRATE: in Aluker ® with cast iron grid

DOOR: rise n'fall with alass ceramic heat resistant up to 750°C, may also be opened

as hinged door for cleaning

PRIMARY AIR: adjustable by hand

SECONDARY AIR: pre-determined

SMOKE DAMPER: automatic and adjustable

ASH DRAWER: removable

HEATING: natural convection

or forced air circulation by

Multifuoco System ® on request, with

1 or 2 ventilators.

FLUE OUTLET: Ø 25 cm

NOMINAL OUTPUT: 13,5 kW

THERMAL EFFICIENCY: 78.5 %

NOMINAL CONSUMPTION: 4 kg/h

MAX OUTPUT: 14,6 kW

MAX CONSUMPTION: 4.6 kg/h

WEIGHT: 285 kg

Laboratory measurements were made using beech wood with moisture content below 20%

Type approval in accordance with EN13229


OPTIONAL ACCESSORIES:


- ventilation kit Multifuoco System® with automatic or manual switching on and off and 4-speed remote control.
- sensor kit for dual Multifuoco System®
- adjustable height kit

DIMENSIONI:

	IG90 ME90/44	
A	24	43
В	93	95,5
С	12,5	19,5
<u>C</u> Ø	15	25

Measurements expressed in cm





www.piazzettadesign.com