



PALEO

Piazzetta  design

Gas fireplace with hand-worked earthenware surround. Expert craftsmanship has gone into making the earthenware ornamentation.

SURROUND WEIGHT: 22 kg

GAS BURNING (NATURAL GAS OR LPG) IG 70

INLET: in grey enamelled steel
 FIREBOX: in Aluker®
 GLASS: ceramic heat resistant up to 750°C
 FUNCTION CONTROL: remote control
 CERAMIC LOGS: standard supply
 HEATING: convection and radiation
 FLUE GAS OUTLET: concentric pipe Ø 10/15 cm
 FIREBOX HEAT OUTPUT: 8.3 kW (Natural gas)
 8.5 kW (LPG)
 THERMAL EFFICIENCY: 80% (Natural gas)
 75% (LPG)
 CONSUMPTION AT RATED HEAT OUTPUT:
 0.79 m³/h (Natural gas)
 640 g/h (LPG)
 WEIGHT: 75 kg
 RATED HEAT OUTPUT: 6 kW (Natural gas)
 5.7 kW (LPG)
 TYPE-EXAMINATION: EC certification E0780

OPTIONAL ACCESSORIES:

- river pebles
- height regulation kit

WOOD BURNING 600 HT

INLET: in black enamelled steel;
 also available in version with door frame
 in shot-peened stainless steel
 FIREBOX: Aluker®
 GRATE: in cast iron
 DOOR: rise n' fall with glass ceramic
 heat resistant up to 750°C, may also be
 opened as hinged door for cleaning
 PRIMARY AIR: pre-determined
 SECONDARY AIR: pre-determined
 SMOKE DAMPER: adjustable externally
 ASH DRAWER: removable
 HEATING: natural convection
 or forced air circulation by
 Multifuoco System® on request
 FLUE OUTLET: Ø 20 cm
 NOMINAL OUTPUT: 10 kW
 THERMAL EFFICIENCY: 74%
 NOMINAL CONSUMPTION: 3.5 kg/h
 MAX OUTPUT: 16,3 kW
 MAX CONSUMPTION: 5,5 kg/h
 WEIGHT: 190 kg
 Laboratory measurements were made using
 beech wood with moisture content below 20%
 Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System
 with automatic or manual switching on and
 off and 4-speed remote control.

WOOD BURNING ME 70/51

INLET: in enamelled steel
 FIREBOX: in Aluker®
 GRATE: in Aluker® with cast iron grid
 DOOR: rise n' fall in enamelled steel
 with glass ceramic heat resistant up to 750°C,
 may also be opened as hinged door for
 cleaning
 PRIMARY AIR: adjustable by hand
 SECONDARY AIR: pre-determined
 SMOKE DAMPER: automatic and adjustable
 ASH DRAWER: removable
 HEATING: natural convection
 or forced air circulation by
 Multifuoco System® on request
 FLUE OUTLET: Ø 20 cm
 NOMINAL OUTPUT: 11 kW
 THERMAL EFFICIENCY: 80%
 NOMINAL CONSUMPTION: 2,9 kg/h
 MAX OUTPUT: 13,8 kW
 MAX CONSUMPTION: 3,8 kg/h
 WEIGHT: 260 kg
 Laboratory measurements were made using
 beech wood with moisture content below 20%
 Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System
 with automatic or manual switching on and
 off and 4-speed remote control.
- sensor kit for dual Multifuoco System
- adjustable height kit

WOOD BURNING MA 260

INLET: in enamelled steel
 FIREBOX: in Aluker®
 GRATE: in cast iron
 DOOR: (optional hinged opening door
 in enamelled steel with glass ceramic
 heat resistant up to 750°C)
 PRIMARY AIR: not present
 (adjustable by hand)
 SECONDARY AIR: not present
 (adjustable by hand)
 SMOKE DAMPER: adjustable externally
 ASH DRAWER: removable
 HEATING: convection
 and radiation
 FLUE OUTLET: Ø 20 cm
 NOMINAL OUTPUT: 8 kW
 THERMAL EFFICIENCY: 51 (59) %
 NOMINAL CONSUMPTION: 3.6 (3.2) kg/h
 WEIGHT: 120 (135) kg
 Laboratory measurements were made using
 beech wood with moisture content below 20%
 Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- glass door kit.
 - Log grate.
- NOTE: features and technical data
 related to the version with glass door kit
 are given in brackets

DIMENSIONI:

	IG70	600 HT	ME70/51	MA260
A	42	62	65,5	60
B	73	84	75,5	80
C	11	25	19,5	18
Ø	15	20	20	20

Measurements expressed in cm

