



SEATTLE

Piazzetta  design

# SEATTLE

Wood burning fireplace with handmade majolica surround. Available in right or left corner

SURROUND WEIGHT: 86 kg

WOOD BURNING: ME 90/44 D/S

INLET: in enamelled steel

FIREBOX: in Aluker<sup>®</sup>

GRATE: in Aluker<sup>®</sup> with cast iron grid

DOOR: rise n' fall with glass ceramic heat resistant up to 750°C, may also be opened as hinged door for cleaning

PRIMARY AIR: adjustable manually

SECONDARY AIR: pre-determined

SMOKE DAMPER: automatic and adjustable

ASH DRAWER: removable

HEATING: natural convection or forced air circulation by Multifuoco System<sup>®</sup> on request, with 1 or 2 ventilators.

FLUE OUTLET: Ø 25 cm

NOMINAL OUTPUT: 13 kW

THERMAL EFFICIENCY: 76,5 %

NOMINAL CONSUMPTION: 3,8 kg/h

MAX OUTPUT: 14 kW

MAX CONSUMPTION: 4,4 kg/h

WEIGHT: 285 kg

Laboratory measurements were made using beech wood with moisture content below 20%  
Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System<sup>®</sup> with automatic or manual switching on and off and 4-speed remote control.
- sensor kit for dual Multifuoco System<sup>®</sup>
- adjustable height kit

